Triton™ Y Style Fabricated Strainer

How To Order

Mechanical Specifications

Example : **F 12 Y RF 1-CS-S4 4-LP**

Product Type
F: Fabricated Strainer

Nominal Pipe Size

Strainer Type
Y: Y-style (wye)

End Connection:
RF: Raised Face Flange
FF: Flat Face Flange
BW: Butt weld
GR: Grooved
X: Custom/Special

ASME Pressure Class:
1: 125 4: 300
2: 150 5: 600
3: 250 X: Custom/Special

Strainer Options
(add appropriate digits as needed)
L: Cover Lifting Lugs
N: Non-standard gasket
P: Differential Pressure Gauge (0-5 psi)
X: Custom

Perforation Size
1: 1/16” 4: 1/4”
2: 1/8” 5: 3/8"
3: 3/16” X: Custom/Special

Strainer Screen Material
S4: 304 Stainless Steel
S6: 316 Stainless Steel
DS: 2205 Duplex SS
X: Custom/Special

Body Material
CS: Carbon Steel
S4: 304 Stainless Steel
S6: 316 Stainless Steel
X: Custom

Example : **F 12 Y RF 1-CS-S4 4-LP**

Fabricated strainer, 12-inch diameter nominal pipe size, Y-style, raised face flange end connections, ASME Class 125, carbon steel body, 304 stainless steel screen, 1/4” holes, lifting lugs on cover, and differential pressure gauge.